

In the claims:

1. (Currently Amended) A device for compressing the chest of a patient comprising:

- a belt adapted to extend at least partially around the chest of the patient and fastened on the patient;
- a belt tensioning means operably connected to the belt for repeatedly tightening and loosening the belt around the chest of the patient;
- a motor operably connected to the belt tensioning means, said motor capable of operating the belt tensioning means repeatedly to cause the belt to tighten about the chest of the patient and loosen about the chest of the patient;
- a brake operably connected to the belt tensioning means and capable of holding the belt tensioning means in a tightened state about the chest of the patient;
- a controller for controlling operation of the motor and brake, said controller programmed to operate the motor and brake to cause repeated cycles of tightening of the belt to a set threshold of tightness, momentarily hold the belt at this threshold of tightness, and release the belt.

2. (Original) A device for compressing the chest of a patient comprising:

- a belt adapted to extend around the chest of the patient and fastened on the patient;
- a drive spool operably connected to the belt and adapted to rotate and take up the belt;

212/369

a motor operably connected to the drive spool, said motor capable of operating the drive spool repeatedly to cause the belt to tighten about the chest of the patient and loosen about the chest of the patient;

a brake operably connected to the drive spool and capable of preventing the drive spool from rotating;

a controller for controlling operation of the motor and brake, said controller programmed to operate the motor and brake to rotate the drive spool to cause repeated cycles of tightening of the belt to a set threshold of tightness, momentarily hold the belt at this threshold of tightness, and release the belt.

3. (Currently Amended) A device for compressing the chest of a patient comprising:

a belt adapted to extend around the chest of the patient and fastened on the patient;

a drive spool operably connected to the belt and adapted to rotate and take up the belt;

a motor operably connected to the drive spool, said motor capable of operating the drive spool repeatedly to cause the belt to tighten about the chest of the patient and loosen about the chest of the patient;

a brake operably connected to the drive spool and capable of preventing the drive spool from rotating;

a controller for controlling operation of the motor and brake, said controller programmed to operate the motor

212/369

and brake to rotate the drive spool to cause repeated cycles of tightening of the belt, ~~and prevent the drive spool from rotating at selected points in the repeated cycles~~ and momentarily hold the drive spool in a braked condition during periods of each cycle.

4. (Currently Amended) The device of claim 1 wherein the brake is further characterized in that it is operable to engage the belt tensioning means ~~at any point in the movement of the belt tightening means~~ to momentarily prevent movement of the belt in order to maintain a higher intrathoracic pressure in the patient's chest.

5. (Currently Amended) The device of claim 2 wherein the brake is further characterized in that it is operable to engage the drive spool ~~at any point in the movement of the drive spool to~~ momentarily prevent movement of the belt in order to maintain a higher intrathoracic pressure in the patient's chest..

6. (Currently Amended) The device of claim 3 wherein the brake is further characterized in that it is operable to engage the drive spool ~~at any point in the movement of the drive spool to~~ momentarily prevent movement of the belt in order to maintain a higher intrathoracic pressure in the patient's chest.

7. (Currently Amended) The device of claim 1 wherein the brake is further characterized in that the brake is operable ~~to continuously slow the movement of the belt tensioning means~~ to hold the belt at a minimum level of belt pressure.

8. (Currently Amended) The device of claim 2 wherein the brake is further characterized in that the brake is operable to

212/369

continuously slow the movement of the drive spool to hold the belt at a minimum level of belt pressure.

9. (Currently Amended) The device of claim 3 wherein the brake is further characterized in that the brake is operable to ~~continuously slow the movement of the drive spool~~ to hold the belt at a minimum level of belt pressure.

10. (Original) The device of claim 1 wherein the controller is programmed to determine the threshold of tightness based on the initial condition of the belt when extended around the chest of the patient.

11. (Original) The device of claim 2 wherein the controller is programmed to determine the threshold of tightness based on the initial condition of the belt when extended around the chest of the patient.

12. (Original) The device of claim 1 wherein the threshold of tightness is determined based on the maximum acceptable torque to be applied by the belt compression means to the belt during operation of the device.

13. (Original) The device of claim 2 wherein the threshold of tightness is determined based on the maximum acceptable torque to be applied by the motor to the drive spool during operation of the device.

14. (Original) The device of claim 1 wherein the threshold of tightness is determined based on the maximum acceptable take-up of the belt during operation of the device.

212/369

15. (Original) The device of claim 2 wherein the threshold of tightness is determined based on the maximum acceptable take-up of the belt during operation of the device.

16. (Original) The device of claim 1 wherein the threshold of tightness is determined based on the measured size of the patient and the allowable change to the circumference of the patient's chest.

17. (Original) The device of claim 2 wherein the threshold of tightness is determined based on the measured size of the patient and the allowable change to the circumference of the patient's chest.